

Expocket Series

휴대용 측정기

Asonе(JAPAN)

고기능 Pocket Size 측정기



● 소형경량으로 휴대에 편리



● Backlight기능



● 손잡이 줄, 보호케이스



● Data Hold

● MAX/MIN/AVG 표시

● AUTO Power OFF기능

Expocket 방사온도계



MODEL	IT-210
측정범위	-30 ~ 550°C
측정정도	±2°C
방사율	0.1 ~ 1.0(가변)
거리	6:1
레이저	1 point
전원	1.5V × 2
규격	50.9×24.7×132.9mm / 120g

Expocket 열전대온도계



MODEL	TM-200(1ch)/TM-201(2ch)
측정범위	-200 ~ +1372°C
측정정도	±0.1%rdg+1°C
샘플링	1회/1초
전원	1.5V × 2
규격	50.9×24.7×132.9mm / 120g

Expocket 온습도계



MODEL	TH-220
측정범위	0~60°C/0~100%RH
측정정도	±0.5°C(10~45°C) ±2.5%RH(10~90%RH)
샘플링	1회/1초
전원	1.5V × 2
규격	50.9×24.7×132.9mm / 120g

Expocket Series

휴대용 측정기

Astone(JAPAN)

Expocket 수분계



MODEL	M-290(수분율) M-291(수분율, 온도, 습도)
측정 범위	8.8~54.8%(M1), 7.0~47.9% (M2), 0.9~22.1%(M3), 0.0~11.0%(M4), 0.7~8.6% (M5), 0.6~9.9%(M6), 0.1~16.5%(M7)
온도	0~60°C/0~100%RH(M-291)
측정 정도	±1%(M-290) ±1%, ±0.5°C, ±2.5%RH(M-291)

Expocket 압력계



MODEL	PM-281
측정 범위	300~1200hPa, 3059~12237mmH ₂ O, 225.0~900.1mmHg
측정 정도	±0.03hPa/0~0.3hPa
표시	mmH ₂ O, mmHg, psi, inH ₂ O, inHg, hPa, mbar, Pa
분해능	0.1hPa, 0.1mmH ₂ O, 0.1mmHg
전원	1.5V × 2
규격	50.9×24.7×132.9mm / 120g

Expocket 차압계



MODEL	DM-280
측정 범위	0~100hPa, 0~1019.7mmH ₂ O, 0~75.00mmHg
측정 정도	±0.03hPa/0~0.3hPa
표시	mmH ₂ O, mmHg, psi, inH ₂ O, inHg, hPa, mbar, Pa, fpm, m/s
분해능	0.01hPa, 0.1mmH ₂ O, 0.01mmHg
전원	1.5V × 2
규격	50.9×24.7×132.9mm / 113g

Expocket 조도계



MODEL	LM-230
측정 범위	0~200,000LUX
측정 정도	±3%rdg+10dgt
샘플링	1회/1초
전원	1.5V × 2
규격	50.9×24.7×132.9mm / 123g

Expocket 풍속계



MODEL	AM-260(풍속, 온도) AM-261(풍속, 온도, 습도)
측정 범위	0.4~20m/s, -10~+50°C 0~100%RH(AM-261)
측정 정도	±2%rdg+0.2m/s, ±0.5°C
전원	1.5V × 2
규격	50.9×24.7×132.9mm / 138g

Expocket 회전계



MODEL	RM-250
측정 범위	100.0~99999rpm
측정 정도	±0.02%rdg+1dgt
샘플링	1회/1초
전원	1.5V × 2
규격	50.9×24.7×132.9mm / 120g