

**FEATURES:**

- 94dB and 114dB Sound Calibration at 1KHz
- Accurate and Simple to use
- Fits 1", 1/2" or 1/4" diameter microphone

SPECIFICATIONS:**Output Sound Pressure Levels:**

114dB and 94dB re 20 uPa under reference conditions.

Output Frequency: 1000Hz $\pm 2\%$

Reference Conditions:

TEMPERATURE $\rightarrow 23^{\circ}\text{C}$ (73°F)

ATMOSPHERIC PRESSURE $\rightarrow 1013$ mbar
(760mm of Hg)

RELATIVE HUMIDITY $\rightarrow 65\%$

Accuracy of Sound Pressure Level:

Under stated reference environment conditions $\pm 0.5\text{dB}$

Power: One 9V battery 006P or IEC 6F22 or NEDA 1604.

Battery Test: Internal circuitry checks condition of battery continuously. Calibrator will operate at all if battery voltage falls below acceptable range.

Battery life: About 20 hours

Dimensions: 103(L) \times 63(W) \times 54(H)mm

Weight: approx. 200g (include batteries)

Operating temperature: $-10 \sim 50^{\circ}\text{C}$ (14 \sim 122°F)

Operating humidity: 0 \sim 90%RH

Accessories: 9V battery, Carrying case, Instruction manual.
1/2" and 1/4" Microphone Adaptor