MColortest[™]

Nitrite Test



1. Method

Determination with color-disk comparator

In acidic solution nitrite ions react with sulfanilic acid to form a diazonium salt, which in turn reacts with N-(1-naphthyl)ethylenediamine dihydrochloride to form a red-violet azo dye. The nitrite concentration is measured **semiquantitatively** by visual comparison of the color of the measurement solution with the color fields of a color disk.

2. Measuring range and number of determinations

Measuring range / color-scale graduation ¹⁾	Number of determinations	
0.1 - 0.2 - 0.4 - 0.6 - 1.0 - 1.8 - 3.0 - 6.0 - 10 mg/l NO ₂ -	400	
0.03 - 0.06 - 0.12 - 0.18 - 0.30 - 0.55 - 0.9 - 1.8 - 3.0 mg/l NO₂-N	400	

¹⁾ for conversion factors see section 8

3. Applications

Sample material:

Groundwater and surface water, seawater Drinking water and mineral water Waters from aquaculture Boiler and boiler feed water, cooling water Wastewater and electroplating wastewater Food after appropriate sample pretreatment Soils after appropriate sample pretreatment

4. Influence of foreign substances

This was checked in solutions containing 1 and 0 mg/l NO_2 . The determination is not yet interfered with up to the concentrations of foreign substances given in the table.

Concentrations of foreign substances in mg/l or %							
Ca ²⁺	1000	Hg ²⁺	100	SiO ₃ ² ·	1000	EDTA	1000
Ca ²⁺ Cd ²⁺	1000	Mg ²⁺	1000	Zn ²⁺	1000	Reducing a	gents
CN ⁻ Cr ³⁺	1000	Mn ²⁺	1000			(ascorbic acid,	
Cr ³⁺	100	NH₄+	1000			sulfite)	10
Cr ₂ O ₇ ²⁻ Cu ²⁺	1	Pb ²⁺	1000			NaCl	20 %
Cu ²⁺	100	PO ₄ 3-	1000			NaNO₃	20 %
Fe³+	1	S ²⁻	10			Na ₂ SO ₄	15 %

5. Reagents and auxiliaries

Please note the warnings on the packaging materials!

The test reagent is stable up to the date stated on the pack when stored closed at +15 to +25 °C.

Package contents:

3 bottles of reagent NO2-1

- 1 graduated 6-ml plastic syringe
- 2 test tubes with screw caps
- 1 colour-disk comparator

Other reagents and accessories:

MQuant™ Nitrite Test, Cat. No. 110007, measuring range 2 - 80 mg/l NO₂· (0.6 - 24 mg/l NO₂·N) MColorpHast™ Universal indicator strips pH 0 - 14, Cat. No. 109535 MColorpHast™ pH-indicator strips pH 0 - 6.0, Cat. No. 109531 Sulfuric acid 0.5 mol/l TitriPUR®, Cat. No. 109072 Sodium hydroxide solution 1 mol/l TitriPUR®, Cat. No. 109137 Nitrite standard solution CertiPUR®, 1000 mg/l NO₂·, Cat. No. 119899

MColortest TM Flat-bottomed tubes with screw caps for MColortest TM with color-disk comparator (12 pcs), Cat. No. 117988

Refill pack:

Cat. No. 118463

Nitrite Test

Refill pack for 114774, 114424, and 114408

(Reagent without technical accessories for the number of determinations stated in section 2)

6. Preparation

- Analyze immediately after sampling.
- Check the nitrite content with the MQuant[™] Nitrite Test.
 Samples containing more than 10 mg/l NO₂ must be diluted with distilled water.
- The pH must be within the range 2 10.
 Adjust, if necessary, with sulfuric acid.
- Filter strongly turbid samples.

7. Procedure

	Measurement sample right-hand tube (A) behind the color disk	Blank left-hand tube (B) behind the color disk	
Pretreated sample (15 - 25 °C)	6 ml	6 ml	Inject into the test tube with the syringe.
Reagent NO ₂ -1	1 level blue microspoon (in the cap of the NO ₂ -1 bottle)	-	Add, close the tube, and shake vigorously until the reagent is completely dissolved. The pH must be within the range 2.0 - 2.5. Check with pH-indicator strips. Adjust the pH, if necessary, with sodium hydroxide solution or sulfuric acid.

Leave to stand for 3 min (reaction time).

Hold the comparator to the light, keeping it upright, and rotate the disk until the closest possible color match is achieved between the two large windows.

Read off the result in mg/I NO₂ shown in the small window.

Notes on the measurement:

- The color of the measurement solution remains stable for at least 60 min after the end of the reaction time stated above.
- Turbidity in the measurement solution makes the color comparison more difficult.
- If the color of the measurement solution is equal to or more intense than the darkest color on the scale, repeat the measurement using fresh, diluted samples until a value of less than 10 mg/l NO₂ is obtained.

Concerning the result of the analysis, the dilution (see also section 6) must be taken into account:

Result of analysis = measurement value x dilution factor

8. Conversions

Units required =	units given	х	conversion factor
mg/I NO ₂ - N	mg/l NO ₂ -		0.304
mg/I NO ₂ -	mg/l NO ₂ -N		<mark>3</mark> .28

9. Method control

To check test reagent, measurement device, and handling:

Dilute the nitrite standard solution with distilled water to 1.0 mg/l NO₂ and analyze as described in section 7.

Additional notes see under www.qa-test-kits.com.

10. Notes

- Reclose the reagent bottle immediately after use.
- Rinse the test tubes and the syringe with distilled water only.
- Information on disposal can be obtained at www.disposal-test-kits.com.

