

# CURRENT CALIBRATOR


Model : CC-422

ISO-9001, CE, IEC1010



**Lutron**

LUTRON ELECTRONIC



*The Art of Measurement*

# CURRENT CALIBRATOR

## Model : CC-422

### FEATURES

* Provide the quality and accuracy of handheld calibrator of precision current source.	* Portable instrument for calibrating process devices and measuring process signals.
* Adjustable 0-24 mA current source, 2 ranges.	* Current calibrator drives loads up to 500 ohms.

### GENERAL SPECIFICATIONS

Display	LCD display, max. display counts 1999. 13 mm ( 0.5" ) digit size.	Operating Humidity	Less than 80% RH.
Function	mA Current source, 2 ranges. 0 - 19.99 mA x 0.01 mA. 0 - 24.0 mA x 0.1 mA.	Power Supply	006P DC 9V, MN1604/PP3 battery or equivalent. Alkaline type or heavy duty type.
Sampling Time	Approx. 0.4 second.	Dimension	185 x 78 x 38 mm ( 7.3 x 3.0 x 1.5 inch ).
Operating Temperature &	0 °C to 50 °C ( 32 °F to 122 °F ). Less than 80% RH.	Weight	265 g/0.58 LB ( including battery ).
		Accessories Included	Operational manual..... 1 PC. Cable with the alligator pairs ( red & black ), LN-TL421..... 1 PC.

### ELECTRICAL SPECIFICATION ( 23 ± 5 °C )

Range	Display Resolution	Accuracy
0 - 19.99 mA	0.01 mA	± ( 0.25 % FS + 1 d )
0 - 24 mA	0.1 mA	± ( 0.5 % FS + 1 d )

\* FS : full scale

\* Appearance and specifications listed in this brochure are subject to change without notice.

0408-CC422