

# 3 PHASE ROTATION TESTER

**Model : RT-606**

*ISO-9001, CE, IEC1010*



**Lutron**













**LUTRON ELECTRONIC**

*The Art of Measurement*

# 3 PHASE ROTATION TESTER

**Model : RT-606**

SPECIFICATIONS	
Signal Input Voltage	100 V AC up to 660 V AC max., 3 min. limit for over 500 V AC.
Signal Current Consumption	7 mA at 500 V AC.
Signal Frequency Range	45 to 70 Hz.
Power Supply	None
Circuit structure	Electronic (not mechanical).
Operating Temperature	0 to 50°C (32 to 122 °F).
Operating Humidity	Less than 90% RH.
Size	100 x 50 x 25 mm. 3.9 x 1.9 x 1.0 inch.
Weight	150 g / 0.33 lb.
Standard Accessories	* Operation manual.....1 PC. * 40 cm length test lead with alligator clip.....3 PCs.

OPERATING INDICATOR INSTRUCTION		
CLOCKWISE (CORRECT)	LIGHT 	L1    L2    L3 
COUNTER CLOCKWISE (CORRECT)	LIGHT 	L1    L2    L3 
L1 NO CONNECT (INCORRECT)	LIGHT 	L1    L2    L3 
L2 NO CONNECT (INCORRECT)	LIGHT 	L1    L2    L3 
L3 NO CONNECT (INCORRECT)	LIGHT 	L1    L2    L3 
Remark	Light ON =  Light OFF = 	

\* Appearance and specifications listed in this brochure are subject to change without notice.